

SURFACE MAX[®]

UTILITY



ALP[®] Supply Surface Max[™] Utility is a premium, non-staining, chemically active, highly refined mineral oil-based form release. This environmentally compliant release agent produces a smooth, void free concrete surface for both indoor and outdoor applications. Recommended for underground and utility precast such as structural prestress products, drainage structures, barriers, vaults and junction boxes.

PRODUCT HIGHLIGHTS

- Ensures easy stripping of forms
- Reduces bug holes and extends the life of most forming materials
- No cleaning between pours necessary
- Chemical release is not harmful to the form or the concrete surface
- Will not retard, etch, or soften concrete surface
- Inhibits rust formation on steel forms
- Low odor

Compatible with a wide range of forming material such as aluminum, plywood, plastic, steel, plyform and more.

Tips for best results: Apply form release in a thin uniform film with a sprayer, brush or roller. Avoid pounding or puddling by not over applying. Colder temperatures will increase the viscosity of Surface Max Utility.

Standards: Meets the requirements of Corps of Engineers Specifications CW 03101, section 2. 1. 2. VOC Compliant and Conforms to the Ozone Transportation Commission (OTC) guidelines for VOC regulations. VOC content is less than 250 g/L. Complies with USA and Federal AIM VOC standards. NYSDOT approved for state projects.

Part Number	Container	Weight (lbs)
FRSMUP	5 Gallon Pail	40
FRSMUD	55 Gallon Drum	430
FRSMUT	275 Gallon Tote	2,120

